

PRODUCT DATA SHEET · EN

FOS Blinder Innovative

IP65 LED blinder with 4 modules

LED blinder with four 100 W warm white 3000 K sources, offering a powerful blinder and strobe effect, controlled via DMX or in Master / Slave mode.

4 × 100 W	IP65	60°	10.9 kg
LIGHT SOURCE	PROTECTION RATING	BEAM ANGLE	WEIGHT

Key features

- Powerful blinder and strobe effect
- Various dimming curves and independent control of the LEDs
- DMX control and Master / Slave modes, DMX channel modes: 1, 3, 4, 9 and 10
- Convection cooling through a heatsink, no fans
- Temperature sensor at each LED, temperature readout in the menu
- On-screen menu operated with four buttons

Technical data

Voltage	90/260 V AC, 50/60 Hz
Power consumption	max. 400 W
Light source	4 × 100 W LED, warm white (3000 K)
Illuminance	1300 lx at a distance of 5 m
Beam angle	60° for each LED source
Control	DMX, Master / Slave
DMX channels	1, 3, 4, 9 and 10
Cooling	heatsink, convection, no fans
Protection rating	IP65
Dimensions	380 × 380 × 190 mm
Weight	10.9 kg

Documentation

User manual PL and original EN
on the product page →

Manufacturer's original manual
EN, fos-lighting.eu →

⚠ **Before using the unit, read the entire user manual and follow the safety instructions.**

Manufacturer and distributor

MANUFACTURER

FOS Technologies LTD

Bulevard Iliensko Shose 8, Sladova Baza ZMM
Sofia, Bulgaria
info@fos-lighting.eu · www.fos-lighting.eu

DISTRIBUTOR IN POLAND

VEX Systems

Media Rental Oleksandr Zakariya
al. Niepodległości 20/55, 02-653 Warszawa, Poland
NIP 5214048857 · +48 794 797 959
biuro@vex-systems.pl · vex-systems.pl