

PRODUCT DATA SHEET · EN

ICON PTZ HD NDI

HD PTZ camera with NDI | HX, PoE

NDI | HX PTZ camera with 20X optical zoom and Full HD 1080p50/60 video, powered via PoE or a 12 V supply. The guide covers installation and connection.

Full HD 1080p50/60	20X	58.7°
RESOLUTION	OPTICAL ZOOM	VIEWING ANGLE

Key features

- PoE power (802.3 af PoE switch) or DC IN 12V connector
- Connectors: LAN, HDMI, 3G-SDI, USB 2.0, RS-422, RS-232 IN/OUT
- IR select (1, 2, 3) on the rear panel
- NDI | HX source for NDI Studio Monitor, vMix and OBS
- Configuration in a web browser at the camera IP address
- H.264 video encoding and AAC audio



Front and rear view
Manufacturer's drawing, labels in EN

Technical data

Resolution	Full HD 1080p50/60
Optical zoom	20X
Viewing angle	58.7°
Default camera IP address	192.168.1.118
DHCP	disabled by default
Recommended computer IP	192.168.1.100
Power	PoE 802.3 af or DC IN 12V
NDI | HX video encoding	H.264 only
NDI | HX audio encoding	AAC only
Required vMix	version 23 or newer
Default user and password	admin

Documentation

User manual PL and original EN
on the product page →

Manufacturer's original manual
EN, fos-lighting.eu →

> ⚠ **Before using the camera, read the whole manual and follow the safety rules.**

Manufacturer and distributor

MANUFACTURER

FOS Technologies LTD
Bulevard Iliensko Shose 8, Sladova Baza ZMM
Sofia, Bulgaria
info@fos-lighting.eu · www.fos-lighting.eu

DISTRIBUTOR IN POLAND

VEX Systems
Media Rental Oleksandr Zakariya
al. Niepodległości 20/55, 02-653 Warszawa, Poland
NIP 5214048857 · +48 794 797 959
biuro@vex-systems.pl · vex-systems.pl