

PRODUCT DATA SHEET · EN

FOS F-11

RGBAWL LED projector, IP65

IP65-rated RGBAWL LED projector with an 84 × 12 W light source and a peak luminous flux of 36000 lm.

84 × 12 W	36000 lm	IP65	9.5 kg
LIGHT SOURCE	PEAK OUTPUT	PROTECTION RATING	NET WEIGHT

Key features

- CCT and dimming adjustment using the knobs or via DMX.
- 25° beam angle, up to 60° with electronic frost.
- 16-bit dimmer: linear dimming without colour shift.
- DMX, Master-Slave and wireless DMX modes; DMX 512 input with 3-pin XLR connectors.
- Die-cast heatsink and controlled fans.
- Overheat protection with a temperature sensor.

Technical data

Light source	84 × 12 W RGBAWL LED
Peak luminous flux	36000 lm
CCT range	1500K-15000K
CRI, TLCI and R9	average CRI, TLCI and R9 95+
Beam angle	25°, up to 60° with electronic frost
DMX modes	2/3/4/11/13/19 channels
LED refresh rate	1.1k/2.2k/11k/37k Hz
Power supply	AC 100-240 V, 50/60 Hz, 800 W
LED source lifetime	over 20 000 hours
Protection rating	IP65
Dimensions	558 × 160 × 323 mm
Net weight	9.5 kg

Documentation

User manual PL and original EN
on the product page →

Manufacturer's original manual
EN, fos-lighting.eu →

> ⚠ **Read the entire user manual and follow the safety rules before using the fixture.**

Manufacturer and distributor

MANUFACTURER

FOS Technologies LTD

Bulevard Iliensko Shose 8, Sladova Baza ZMM
Sofia, Bulgaria
info@fos-lighting.eu · www.fos-lighting.eu

DISTRIBUTOR IN POLAND

VEX Systems

Media Rental Oleksandr Zakariya
al. Niepodległości 20/55, 02-653 Warszawa, Poland
NIP 5214048857 · +48 794 797 959
biuro@vex-systems.pl · vex-systems.pl